

Vibration transducers and accessories

Norsonic has a carefully selected range of single and triaxial accelerometers.

All accelerometers are piezoelectric charge type with integral preamplifier, so called IEPE or ICP accelerometers.

General purpose single axis accelerometer Nor1270

Nor1270 is a general purpose accelerometer for industry and laboratory use.



Triaxial seat pad accelerometer Nor1286

This triaxial seat accelerometer is designed for whole body measurements according to ISO2631 and ISO8041. The integral cable is 2m and the connector fits the Nor133 and Nor136 vibration meters. The seat pad consists of a rubber pad, an aluminum mounting adapter plate to where a triaxial accelerometer type Nor1288 is mounted. The Nor1288 accelerometer port is detachable for calibration purpose.



Triaxial miniature accelerometer Nor1287

This accelerometer is designed for hand arm vibration measurements according to ISO5349 and ISO8041 as well as general vibration measurements. The small physical dimensions and weight ensures low influence and easy mount on the measurement object.



Triaxial accelerometer Nor1288

The triaxial accelerometer Nor1288 is designed for general vibration measurements and as a reference accelerometer when conducting whole body measurements using the 6 channel vibration meter Nor136. The Nor1288 is then mounted on the vehicle itself and the correlation between the vehicle vibrations and the drivers seat can be measured.



Triaxial Velocity Sensor (Geophone) Nor1292

32 mV/mms-1. 3-axial passive velocity transducer has screw-adjustable feet and libelle for horizontal alignment. With 2 m cable and 7 pin LEMO connector.



Accessories:

Microdot cable Nor1480 (1,5m) and Nor1481 (5m)

Microdot-microdot cable suitable for use on accelerometer Nor1270 and Nor1271.

Triaxial cable Nor4551

1,5m cable for connecting a Norsonic triaxial accelerometer to Nor133 / Nor136 vibration meters, fitted with 4 pin MicroCom connectors.

Triaxial cable Nor4555

1,5m cable for connecting a Norsonic triaxial accelerometer to Nor133 / Nor136 vibration meters, fitted with 4 pin Lemo connectors.

Triaxial cable Nor4556

5m cable for connecting a ZEB/GS3T Geophone to Nor136 vibration meters

TNC to microdot adapter, Nor1456

BNC to microdot adapter, Nor1466

	Nor1270	Nor1286	Nor1287	Nor1288	Nor1292	Units
Physical						
Type	Single-share	Triaxial-share	Triaxial-share	Triaxial-share	Triaxial passive geophone	
Weight	23	227	4	14	2500	gram
Size [1]	Ø17x17	Ø=232x12 (9,16X0,74)	12x9,1x9,1 (0,49x0,36x0,36)	21x21x8,6 (0,82x0,82x0,34)	140x140x95 (5,5x5,5x3,74)	mm - (inch)
Material	Stainless steel	Rubber/ Anodized aluminum/ Titanium Alloy	Titanium Alloy	Titanium Alloy	Steel	
Connector	Microdot	4 pin Microcom	4 pin Microcom	4 pin Microcom	7 pin Lemo	
Cable length	-	2 (78)	-	-		M (inch)
Mounting	Tapped hole in base for 5mm screw	-	Tapped hole in base for 3 mm screw	Through hole for 4 mm screw	3 x spikes	
Performance						
Sensitivity each axis ±5% [2]	100	100	10	100	26 mv/mmS	mv/g
Range F.S. for ±5V output	±50	±50	±500	±50		G
Frequency range ±5%	0,4 – 18k	0,5-3k	1,5 – 10k	0,5-3k	1 - 500	Hz
Resonance frequency nom.	>32k	25k	40k	25k	4,5	Hz
Equivalent electrical noise floor	0,0003	0,0007	0,007	0,0007		Grms
Linearity [3]	-	±1%	±1%	±1%		% F.S.
Transverse sensitivity max.	5	5	5	5		%
Environmental						
Maximum vibration/Shock	-/6000	400/1500	600/5000	600/1500		± G's/G's PEAK
Temp. range operation	-20 to +120 -4 to + 248	-50 to +70 -60 to +160	-50 to +120 -60 to +250	-50 to +120 -60 to +250	-40 +70	°C °F
Temp range survival	-	-70 to +135 -100 to +275	-70 to +135 -100 to +275	-70 to +135 -100 to +275	-40 +70	°C °F
Seal accelerometer	Hermetic	Hermetic	Hermetic	Hermetic		
Coefficient of thermal sensitivity	±0,02	0,05	0,05	0,05		%/ °K
Electrical						
Supply current [4]	2-20	2-20	2-20	2-20		mA
Compliance supply voltage	+20 to +30	+18 to +30	+18 to +30	+18 to +30		VDC
Bias voltage range	+12 to +14	+9 to +12	+9 to +12	+9 to +12		VDC
Output impedance, Typ.	<130	<100	<100	<100	312	Ohms
Discharge time constant	-	0,8 – 1,2	0,3	1,0		Sec.
Signal polarity						
Electrical insulation for case ground to mounting surface	Case grounded	>10	Case grounded	>10		Mohm

Specifications subject to changes without notice.

- [1] Measures are without cable or connector
- [2] Measured at 100 Hz, 1 G RMS per ISA RP 37.2.
- [3] Measured using zero-based best straight line method, % of F.S. or any lesser range.
- [4] Do not apply power to this device without current limiting, 20 mA MAX.
To do so will destroy the integral IC amplifier.

Distributor: